

Saba Lighting

WP100

IP65



FEATURES

LISTING

- ETL listed IP65 rating for outdoor use

HOUSING

- Diecast cooling design, better cooling light quality

LEDS

- New generation LED technology

FINISH

- UV stabilized powder coated finish

LENS

- Excellent optical design, greatly improve the light utilization and evenness.

- Heat and impact resistant polycarbonate lens

OPTIONS

- Available with dust to dawn photocell sensor

Utilizing the latest generation of LED chips, this uniquely designed wall pack delivers a similar light output from 150W to 600W metal halide but with only 1/4 energy consumption. Housing made of die-casting aluminum with reliable powder coating specifically for harsh outdoor environment. It is attractive in appearance and performance.

Optional Add-Ons



Button Photo Control

SKU: PC-B120 (120V)
PC- B277 (277V)

SPECIFICATIONS

Model No.	WP100			
System Watts	40	60	120	150
Lumen Output	5200lm	7650lm	16022lm	18980lm
Color Temp (T)	50=5000K(Std) 30=3000K*, 40=4000K*			
Input Voltage (V)	A = 120~277V B = 347~480V			
CRI	70+			
Operating Temp	-40°C - 60°C			
MH Equivalent	150W	200W	400W	600W
SKU	WP100-T70-40V	WP100-T70-60V	WP100-T70-120V	WP100-T70-150V

DIMENSIONS

